

W1110 Digital Projector



Features

- 6-Segment Color Wheel with 6X Speed
- 1.3X zoom short-throw lens
- Vertical lens shift
- CinemaMaster Audio Enhancer
- ISFccc
- New Friendly UI
- Optional Wireless FHD kit

Box Contents

- Lens Cover
- Remote Control with Battery
- Power Cord (by region)
- User Manual CD
- Quick Start Guide
- Warranty Card (by region)

Dimension




Optional Accessories

- 3D Glasses (DGD5)
- Spare Lamp Kit
- Ceiling Mount
- Carry Bag
- Wireless FHD Kit (WDP01)



Because it matters

Input and Output Terminals



- 1 HDMI input ports
- 2 I2VDC output terminal
Used to trigger external devices such as an electric screen or light control, etc. Consult your dealer for how to connect these devices.
- 3 USB Type-A port
Used for charging the receiver box of the Wireless FHD Kit (WDP01) (optional accessory).
- 4 Mini USB port
Used for service.
- 5 RGB (PC)/Component video (YPbPr/YCbCr) signal input jack
- 6 RS-232 control port
Used to interface with a PC or home theater control/automation system.
- 7 Component Video inputs (RCA)
Support Y/PB/PR or Y/CB/CR video signal.
- 8 Video input jack
- 9 Audio (L/R) input jacks
- 10 Audio input jack
- 11 Audio output jack
- 12 Speaker grill
- 13 AC Power cable inlet
- 14 Rear adjuster foot

Product Specifications

Projection System	DLP
Native Resolution	1080p (1920 x 1080)
Brightness	2200 ANSI Lumen
Contrast Ratio	15000:1
Display Color	1.07 Billion Colors
Lens	F=2.59-2.87, f=16.88-21.88mm
Aspect Ratio	Native 16:9 (5 aspect ratio selectable)
Throw Ratio	1.15-1.5 (100"@2.5m)
Image Size (Diagonal)	60"-180"/300"
Zoom Ratio	1.3:1
Lamp Type	240W
Lamp Mode (Normal/Eco/SmartEco/LampSave)*	3500/5000/6000 hours
Keystone Adjustment	Manual vertical ± 4 degrees
Projection Offset	105% $\pm 2.5%$ / Vertical : +10%
Resolution Support	VGA(640 x 480) to WUXGA_RB(1920 x 1200) *RB=Reduced blanking
Horizontal Frequency	15~102KHz
Vertical Scan Rate	23-120Hz
Color Wheel Segment	6-Segment (RGBRGB)
Color Wheel Speed	6X (50Hz)
Compatibility	HDTV Compatibility 480i, 480p, 576i, 567p, 720p, 1080i, 1080p Video Compatibility NTSC, PAL, SECAM, SDTV 3D Compatibility Frame Sequential: Up to 720p (Please refer to User's Manual for detailed support timing.) Frame Packing: Up to 1080p Side by Side: Up to 1080i/p Top Bottom: Up to 1080p
Interface	Computer in (D-sub 15pin) x 1 Composite video in (RCA) x 1 Component video in x 1 HDMI x 2 Audio in (Mini Jack) x 1 Audio L/R in (RCA) x 1 Audio out (Mini Jack) x 1 Chamber Speaker 10W x 1 USB (Type A) x 1 (5V/1.5A power supply) USB (Type Mini B) x 1 (service) RS232 (DB-9pin) x 1 DC 12V Trigger x 1 IR receiver x 2 (Front & Top)
Dimensions	Dimensions(W x H x D) 380.5 x 121.7 x 277 mm Weight 3.3 kg
Power	Power Supply AC 100 to 240V, 50 to 60 Hz Power Consumption Normal : 353W, Eco : 292W, Standby < 0.5W
Audible Noise	29/27 dBA (Normal/Economic mode)
On-Screen Display Languages	Arabic/Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese (28 Languages)
Picture Modes	** ISF Disabled: Bright/Vivid/Cinema/Game//User 1/User 2/(3D) *** ISF Enabled: Bright/Vivid/Cinema/Game/User 1/User 2/ISF Night/ISF Day/(3D)
Environmental Notice	Lamp in this product contains mercury. To dispose of the product or used lamps, consult your local environment authorities for regulations or see www.lamprecycle.org .

*Lamp life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.

** Default picture mode is Standard. When 3D is on, picture mode menu only show 3D. When 3D is off, 3D will also disappear.

*** When ISF is enable, default picture mode is ISF Night. When 3D is on, picture mode only show 3D. When 3D is off, 3D will also disappear.

Logistics information

Product Code	9HJEE77.17E
EAN Code	471 8755 06051 9
Dimensions Single Carton (cm)	49.5 * 20 * 35.3
Carton Weight (kg)	4,8
Pallet Size Block (cm)	120*100*188.5



BenQ Europe B.V.
Meerenakkerweg 1-17
5652 AR Eindhoven
The Netherlands
Tel: +31 88 8889200
Fax : +31 88 8889299

© 2015 BenQ Corp. Specification may vary by region, please visit your local stores for details.
Actual product's features and specifications are subject to change without notice.
This material may include corporate names and trademarks of third parties which are the properties of the third parties respectively. Doc.: PRJ HB BR EN 0301



Because it matters